



M101-0143 TONE FINISH RAW UMBER

# MATERIAL SAFETY DATA SHEET

RPM Wood Finishes Group  
3194 Hickory Boulevard  
Hudson, North Carolina 28638  
828-728-8266

EMERGENCY PHONE (CHEM TREC): ..... 1-800-424-9300  
FOR ALL INTERNATIONAL TRANSPORTATION ACCIDENTS. .... 1-703-527-3887 (collect)

Health: 2                      Flammability: 4                      Reactivity 0

PRODUCT NAME: M101-0143 TONE FINISH RAW UMBER

## I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

|                  |  |
|------------------|--|
| REVISION DATE:   | 15/09/06   |
| SUPERCEDES:      | 15/03/06   |
| MSDS NO.         | M101-0143  |
| OSHA HAZ. CLASS: | Eye irritant. Neurotoxin - may cause nervous system damage.<br>Mucous membrane (respiratory tract) irritant. |

## II. COMPOSITION/INFORMATION ON INGREDIENTS

| CHEMICAL NAME                      | %     | CAS #     | PEL                          |
|------------------------------------|-------|-----------|------------------------------|
| acetone                            | 21-30 | 67-64-1   | 1000 ppm TWA; 2400 mg/m3 TWA |
| ethyl acetate                      | 21-30 | 141-78-6  | 400 ppm TWA; 1400 mg/m3 TWA  |
| propane                            | 11-20 | 74-98-6   | 1000 ppm TWA; 1800 mg/m3 TWA |
| n-butyl acetate                    | 11-20 | 123-86-4  | 150 ppm TWA; 710 mg/m3 TWA   |
| isobutane                          | 1-10  | 75-28-5   | No PEL established           |
| toluene                            | 1-10  | 108-88-3  | 200 ppm TWA; C 300 ppm       |
| isopropanol                        | 1-10  | 67-63-0   | 400 ppm TWA; 980 mg/m3 TWA   |
| ROSINESTER                         | 1-10  | 8050-31-5 | No PEL established           |
| isobutyl isobutyrate               | 1-10  | 97-85-8   | No PEL established           |
| Cellulose Nitrate, Cellulose Ester | 1-10  | 9004-70-0 | No PEL established           |
| 1,2,4-trimethylbenzene             | <1    | 95-63-6   | No PEL established           |
| carbon black                       | <1    | 1333-86-4 | 3.5 mg/m3 TWA                |

## III. HAZARDS IDENTIFICATION

**Routes of Entry:** Inhalation, ingestion, skin, eyes.  
**Medical Conditions Aggravated:** Skin disease including eczema and sensitization. Respiratory disease including asthma and bronchitis. Eye disease. Kidney disease. Liver disease.

### Immediate (Acute) Health Effects

**Inhalation:** Irritation may be delayed for several hours. Can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.

|   |   |
|---|---|
| <b>Skin Contact:</b>                              | Substance causes moderate skin irritation. Can cause minor skin irritation, defatting, and dermatitis.  |
| <b>Eye Contact:</b>                               | Can cause irritation. Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue. Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible. No hazard in normal industrial use. |
| <b>Skin Absorption:</b>                           | Can be absorbed through the skin but exposure must be extensive before adverse health effects occur. Harmful if absorbed through the skin. May cause severe irritation and systemic damage. No absorption hazard in normal industrial use.  |
| <b>Ingestion:</b>                                 | Harmful if swallowed. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea.   |
| <b>Target Organ Acute Toxicity:</b>               |   |
| Acetone   | respiratory system, skin, eyes, CNS   |
| Ethylacetate                                      | eyes, skin, respiratory system  |
| Propane   | CNS   |
| n-Butyl acetate                                   | eyes, skin, respiratory system, CNS   |
| Isobutane   | CNS   |
| Toluene   | CNS, liver, kidneys, skin, eyes, respiratory system   |
| Isopropyl alcohol                                 | eyes, skin, respiratory system  |
| 1,2,4-Trimethylbenzene                            | eyes, skin, respiratory system, CNS, blood  |
| Carbon black                                      | respiratory system, eyes, lymphatic cancer  |
| <b><u>Long-Term (Chronic) Health Effects:</u></b> |   |
| <b>Carcinogenicity:</b>                           | ACGIH. IARC. NIOSH. NTP. OSHA. Contains a substance that is a probable cancer hazard based on human studies.  |
| <b>Reproductive and Developmental Toxicity:</b>   | Possible reproductive hazard. No data.  |
| <b>Mutagenicity:</b>                              | No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.   |
| <b>Inhalation:</b>                                | Upon prolonged and/or repeated exposure, can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.  |
| <b>Skin Contact:</b>                              | Prolonged or repeated contact may cause irritation. Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.  |
| <b>Eye Contact:</b>                               | Upon prolonged or repeated contact, can cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.  |
| <b>Skin Absorption:</b>                           | Skin sensitization, characterized by redness, inflammation, itching and/or burning may result from prolonged or repeated contact with this material. Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause severe irritation and systemic damage.  |

**Target Organ Chronic Toxicity:** Respiratory Tract. Skin. Skin. Eyes. Nervous System. Respiratory Tract. Nervous System. Eyes. Kidneys. Liver.

**Supplemental Health Hazard Information:** No additional health information available.

#### **IV. FIRST AID**

---

**Inhalation:** Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately.

**Eyes:** Immediately flush eyes with plenty of water. Get medical attention, if irritation persists. Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.

**Skin Contact:** Wash with soap and water. Get medical attention if irritation develops or persists. Wash with soap and water. Get medical attention if irritation develops or persists.

**Ingestion:** No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS.

**Notes to MD:** No additional first aid information available.

#### **V. FIRE FIGHTING MEASURES**

---

##### **Flammability Summary:**

**Flash Point:** -144 (CALC.) °F  
**Upper Flammable/Explosive Limit, % in air:** 12.8 @ 77° F  
**Lower Flammable/Explosive Limit, % in air:** 1.4 @ 77° F

**Fire Hazards:** Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flash point. Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a Class B fire. Vapors are heavier than air and may travel to a source of ignition and flash back.

**Extinguishing Media:** Use alcohol resistant spray, Carbon Dioxide, water spray or dry chemical to extinguish a fire involving this chemical. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. H<sub>2</sub>O, CO<sub>2</sub>, dry chemical, foam. Carbon dioxide Alcohol foam Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and keep exposed material from being damaged by fire.

**Fire Fighting Instructions:** Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Do not enter fire area without proper protection including self-contained toxic breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling.

**Hazardous Combustion Products:** Carbon dioxide, Carbon monoxide Toxic gases Hydrogen cyanide Nitrogen containing gases

## VI. ACCIDENTAL RELEASE MEASURES

**Health Consideration for Spill Response:** Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

**Spill Mitigation Procedures General Methods:** Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

## VII. HANDLING AND STORAGE

**Handling:** Use spark-proof tools and explosion-proof equipment. Wash thoroughly after handling. Avoid contact with material. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Remove contaminated clothing and wash before reuse. Harmful or irritating material. Avoid contact and avoid breathing the material. Use only in a well ventilated area.

**Storage:** Keep away from heat, sparks, and flame. Keep away from sources of ignition. Keep container closed when not in use. Store in a cool place in original container and protect from sunlight. Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed.

## VIII. ENGINEERING CONTROLS AND PERSONAL PROTECTIVE EQUIPMENT

**Engineering Controls:** Ventilation should effectively remove and prevent buildup of any vapor/mist/fume generated from the handling of this product. Explosion proof exhaust ventilation should be used. Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

### Protective Equipment

**Respiratory Tract:** Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2-1992). A written respiratory protection program, including provisions for medical certification, training, fit testing, exposure assessments, maintenance, inspection, cleaning, and convenient, sanitary storage should be implemented.

**Eyes:** Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available.

**Skin:** Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

## IX. PHYSICAL DATA

|                               |                |
|-------------------------------|----------------|
| <b>Physical State:</b>        | COLORED LIQUID |
| <b>Odor:</b>                  | NGR/ALCOHOLS   |
| <b>Solids Vol %:</b>          | 4.6252         |
| <b>Solids Wt %:</b>           | 7.2816         |
| <b>Material VOC lbs/gal:</b>  | 4.4818         |
| <b>Material VOC gms/l:</b>    | 538.2237       |
| <b>Coatings VOC lbs/gal:</b>  | 5.6979         |
| <b>Coatings VOC gms/l:</b>    | 684.2685       |
| <b>Weight per gallon lbs:</b> | 6.3664         |

VOC data per US EPA guidelines. State and local variations may apply.

## X. STABILITY AND REACTIVITY

|                                  |   |
|----------------------------------|---|
| <b>Stability Information:</b>    | Stable. Normally stable. Keep away from heat, sparks and flame.                 |
| <b>Conditions to Avoid:</b>      | Avoid: heat, sparks, flame and oxidizing agents. High temperatures. None known. |
| <b>Chemical Incompatibility:</b> | Strong oxidizing agents. Strong acids. Strong alkalies. Amines.                 |
| <b>Hazardous Polymerization:</b> | Hazardous Polymerization will not occur.  |

## XI. TOXICOLOGICAL INFORMATION

| Chemical Name                         | CAS Number           | LD50/LC50  |
|---------------------------------------|----------------------|--|
| Acetone                               | 67-64-1              | Inhalation LC50 Rat : 50100 mg/m <sup>3</sup> /8H; Inhalation LC50 Mouse : 44 gm/m <sup>3</sup> /4H; Oral LD50 Rat : 5800 mg/kg; Oral LD50 Mouse : 3 gm/kg                               |
| Acetic acid, ethyl ester              | 141-78-6             | Inhalation LC50 Rat : 200 gm/m <sup>3</sup> ; Inhalation LC50 Mouse : 45 gm/m <sup>3</sup> /2H; Oral LD50 Rat : 5620 mg/kg; Oral LD50 Mouse : 4100 mg/kg; Dermal LD50 Rabbit : >20 mL/kg |
| Acetic acid, butyl ester              | 123-86-4             | Inhalation LC50 Rat : 2000 ppm/4H; Inhalation LC50 Mouse : 6 gm/m <sup>3</sup> /2H; Oral LD50 Rat : 10768 mg/kg; Oral LD50 Mouse : 6 gm/kg; Dermal LD50 Rabbit : >17600 mg/kg            |
| Propane, 2-methyl-Toluene             | 75-28-5<br>108-88-3  | Inhalation LC50 Rat : 57 pph/15M<br>Inhalation LC50 Rat : 49 gm/m <sup>3</sup> /4H; Inhalation LC50 Mouse : 400 ppm/24H; Oral LD50 Rat : 636 mg/kg; Dermal LD50 Rabbit : 14100 uL/kg     |
| Isopropyl alcohol                     | 67-63-0              | Inhalation LC50 Rat : 16000 ppm/8H; Oral LD50 Rat : 5045 mg/kg; Oral LD50 Mouse : 3600 mg/kg; Dermal LD50 Rabbit : 12800 mg/kg   |
| Isobutyric acid, isobutyl ester       | 97-85-8              | Inhalation LC50 Rat : 5000 ppm/6H; Oral LD50 Rat : 12800 mg/kg; Dermal LD50 Rabbit : >8600 mg/kg   |
| Nitrocellulose                        | 9004-70-0            | Oral LD50 Rat : >5 gm/kg; Oral LD50 Mouse : >5 gm/kg   |
| Benzene, 1,2,4-trimethyl-Carbon black | 95-63-6<br>1333-86-4 | Inhalation LC50 Rat : 18 gm/m <sup>3</sup> /4H; Oral LD50 Rat : 5 gm/kg<br>Oral LD50 Rat : >15400 mg/kg; Dermal LD50 Rabbit : >3 gm/kg   |

## XII. ECOLOGICAL INFORMATION

|                                    |   |
|------------------------------------|---|
| <b>Overview (for ingredients):</b> | Keep out of waterways. Moderate ecological hazard. This product may be dangerous to plants and/or wildlife. |
|------------------------------------|---|

### **XIII. DISPOSAL CONSIDERATIONS**

---

**Waste Description for Spent Product:** The waste may be a listed and/or characteristic hazardous waste. The waste may be a listed hazardous waste. The waste may be a "special" waste. Spent or discarded material is a hazardous waste.

**Disposal Methods:** Comply with all Local, State, Federal, and Provincial Environmental Regulations. Dispose of by incineration following Federal, State, Local, or Provincial regulations.

**Potential EPA Waste Codes:** If discarded, this product is considered a RCRA ignitable waste, D001.

**Components Subject to USEPA Land Disposal Restrictions:**

|              |          |         |
|--------------|----------|---------|
| Acetone      | 67-64-1  | 22.16 % |
| Ethylacetate | 141-78-6 | 20.99 % |
| Toluene      | 108-88-3 | 5.44 %  |

### **XIV. TRANSPORTATION INFORMATION**

---

**DOT** AEROSOLS, FLAMMABLE, 2.1, UN 1950  
See 49CFR 172.101 for Special Provisions, Packaging, and Quantity Limitations.

### **XV. REGULATORY INFORMATION**

---

| <b>Chemical Name</b>   | <b>Regulation</b>                                    | <b>CASRN</b> | <b>%</b> |
|------------------------|--|--------------|----------|
| Toluene                | SARA 313 Reportable:                                 | 108-88-3     | 5.44     |
| Isopropyl alcohol      | SARA 313 Reportable:                                 | 67-63-0      | 4.32     |
| 1,2,4-Trimethylbenzene | SARA 313 Reportable:                                 | 95-63-6      | 0.04     |
| sec-Butyl alcohol      | SARA 313 Reportable:                                 | 78-92-2      | 0.01     |
| Benzene, methyl-       | California Proposition 65 Cancer List:               | 108-88-3     | 5.44     |
| Carbon Black           | California Proposition 65 Cancer List:               | 1333-86-4    | 0.03     |
| Quartz                 | California Proposition 65 Cancer List:               | 14808-60-7   | 0.00     |
| Toluene                | California Proposition 65<br>Developmental Toxicity: | 108-88-3     | 5.44     |
| acetone                | New Jersey Right To Know:                            | 67-64-1      | 22.16    |
| ethyl acetate          | New Jersey Right To Know:                            | 141-78-6     | 20.99    |
| propane                | New Jersey Right To Know:                            | 74-98-6      | 14.94    |
| n-butyl acetate        | New Jersey Right To Know:                            | 123-86-4     | 14.74    |
| isobutane              | New Jersey Right To Know:                            | 75-28-5      | 6.77     |

### **XVI. ADDITIONAL INFORMATION**

---

**Other Information:** IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HEREUNDER ARE GIVEN GRATIS. NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

MSDS glossary.