



M506-000 HI Glaze Heavy Bodied Base

# MATERIAL SAFETY DATA SHEET

RPM Wood Finishes Group  
3194 Hickory Boulevard  
Hudson, North Carolina 28638  
828-728-8266

EMERGENCY PHONE (CHEM TREC): ..... 1-800-424-9300  
FOR ALL INTERNATIONAL TRANSPORTATION ACCIDENTS. .... 1-703-527-3887 (collect)

Health: 2                      Flammability: 3                      Reactivity 0

PRODUCT NAME: M506-000 HI Glaze Heavy Bodied Base

## I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

REVISION DATE: 19/09/05  
SUPERCEDES: 10/08/05  
MSDS NO. M506-000

## II. COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	%	CAS #	PEL
linseed oil	21-30	8001-26-1	No PEL established
aromatic hydrocarbons	21-30	64742-95-6	No PEL established
1,2,4-trimethylbenzene	11-20	95-63-6	No PEL established
Organoclay	11-20	68911-87-5	No PEL established
aromatic hydrocarbons	1-10	64742-94-5	No PEL established
1,3,5-trimethylbenzene	1-10	108-67-8	No PEL established
propylene glycol monomethyl ether	1-10	107-98-2	No PEL established
diethylbenzene	1-10	25340-17-4	No PEL established
cumene	<1	98-82-8	50 ppm TWA; 245 mg/m3 TWA
naphthalene	<1	91-20-3	10 ppm TWA; 50 mg/m3 TWA
m-xylene	<1	108-38-3	No PEL established
Quartz	<1	14808-60-7	see Table Z-3
ethylbenzene	<1	100-41-4	100 ppm TWA; 435 mg/m3 TWA
o-xylene	<1	95-47-6	No PEL established
p-xylene	<1	106-42-3	No PEL established

## III. HAZARDS IDENTIFICATION

**Routes of Entry:** Inhalation., Ingestion., Skin contact., Eye contact., Absorption.  
**Medical Conditions Aggravated:** Skin allergies. Kidney disease. Eye disease. Liver disease. Skin disease including eczema and sensitization. Respiratory disease including asthma and bronchitis. Digestive tract disease.

## **Immediate (Acute) Health Effects**

<b>Inhalation:</b>	No hazard in normal industrial use. Moderately irritating to respiratory tract. Causes respiratory tract irritation. Chronic lung disease (silicosis) and/or lung cancer may result from prolonged/repeated breathing of the dust of this material. Can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.
<b>Skin Contact:</b>	Moderately irritating to the skin. Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
<b>Eye Contact:</b>	Can cause moderate irritation. Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
<b>Skin Absorption:</b>	Toxic and may be harmful if absorbed through the skin; may produce target organ damage. Minimal hazard in normal industrial use. May cause gastrointestinal discomfort.
<b>Ingestion:</b>	Small amounts (a tablespoonful) swallowed during normal handling operations are not likely to cause injury; swallowing amounts larger than that may cause injury. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea.

## **Target Organ Acute Toxicity:**

1,2,4-Trimethylbenzene	eyes, skin, respiratory system, CNS, blood
1,3,5-Trimethylbenzene	eyes, skin, respiratory system, CNS, blood
Propylene glycol monomethyl ether	eyes, skin, respiratory system, CNS
Cumene	eyes, respiratory system, skin, CNS
Naphthalene	eyes, blood, liver, kidneys, skin, CNS
m-Xylene	CNS, eyes, blood, liver, kidneys, skin, GI tract, respiratory system
Silica, crystalline	respiratory system, eyes (in animals: lung cancer)
Ethyl benzene	eyes, respiratory system, skin, CNS
o-Xylene	CNS, eyes, blood, liver, kidneys, skin, GI tract, respiratory system
p-Xylene	CNS, eyes, blood, liver, kidneys, skin, GI tract, respiratory system

## **Long-Term (Chronic) Health Effects:**

<b>Carcinogenicity:</b>	ACGIH. IARC. NIOSH. NTP. OSHA. Contains a substance that is a probable cancer hazard based on human studies.
<b>Reproductive and Developmental Toxicity:</b>	A component in this product has been shown to cause birth defects and reproductive disorders in laboratory animals at doses that could be encountered in the workplace. No data.
<b>Mutagenicity:</b>	No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.
<b>Inhalation:</b>	Upon prolonged and/or repeated exposure, can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.
<b>Skin Contact:</b>	May cause lingering affects but not likely to result in permanent damage if the exposure is eliminated. Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

<b>Eye Contact:</b>	Upon prolonged or repeated contact, dust contact can cause mechanical irritation. Upon prolonged or repeated contact, can cause severe irritation. Eye contact may result in corneal injury. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Temporary vision impairment (cloudy or blurred vision) is possible.
<b>Skin Absorption:</b>	Skin sensitization, characterized by redness, inflammation, itching and/or burning may result from prolonged or repeated contact with this material. Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause severe irritation and systemic damage.
<b>Target Organ Chronic Toxicity:</b>	Kidneys. Eyes. Liver. Skin. Nervous System. Respiratory Tract. Digestive Tract. Blood.
<b>Supplemental Health Hazard Information:</b>	No additional health information available.

#### **IV. FIRST AID**

---

<b>Inhalation:</b>	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. This material does not present a hazard if inhaled. Remove individual to fresh air after an airborne exposure if any symptoms develop, as a precautionary measure.
<b>Eyes:</b>	Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.
<b>Skin Contact:</b>	Wash with mild soap and water. If irritation occurs get medical attention. If clothing is contaminated, remove and wash before reuse. Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
<b>Ingestion:</b>	No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS.
<b>Notes to MD:</b>	No additional first aid information available.

#### **V. FIRE FIGHTING MEASURES**

---

##### **Flammability Summary:**

<b>Flash Point:</b>	86 (CALC.) °F
<b>Fire Hazards:</b>	Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.
<b>Extinguishing Media:</b>	H2O, CO2, dry chemical, foam. Dry chemical Foam, water, dry chemical Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire.

**Fire Fighting Instructions:** Use methods for the surrounding fire. Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.

**Hazardous Combustion Products:** Carbon monoxide

## **VI. ACCIDENTAL RELEASE MEASURES**

---

**Health Consideration for Spill Response:** Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

**Spill Mitigation Procedures General Methods:** Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

## **VII. HANDLING AND STORAGE**

---

**Handling:** Use spark-proof tools and explosion-proof equipment. Avoid contact with material. Minimize dust generation and accumulation. Harmful or irritating material. Avoid contact and avoid breathing the material. Use only in a well ventilated area.

**Storage:** Spontaneous combustion can occur. Keep away from sources of ignition. Keep container closed when not in use. Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed.

## **VIII. ENGINEERING CONTROLS AND PERSONAL PROTECTIVE EQUIPMENT**

---

**Engineering Controls:** Ventilation should effectively remove and prevent buildup of any dust generated from the handling of this product. Facilities storing or using this material should be equipped with an eyewash and safety shower. Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

### **Protective Equipment**

**Respiratory Tract:** Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2-1992). A written respiratory protection program, including provisions for medical certification, training, fit testing, exposure assessments, maintenance, inspection, cleaning, and convenient, sanitary storage should be implemented.

**Eyes:** Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available.

**Skin:** Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

## IX. PHYSICAL DATA

---

**Physical State:** COLORED VISCOUS LIQUID  
**Odor:** OILY HYDROCARBON  
**Solids Vol %:** 37.1632  
**Solids Wt %:** 41.2399  
**Material VOC lbs/gal:** 4.6132  
**Material VOC gms/l:** 553.9993  
**Coatings VOC lbs/gal:** 4.6132  
**Coatings VOC gms/l:** 553.9993  
**Weight per gallon lbs:** 7.8687

VOC data per US EPA guidelines. State and local variations may apply.

## X. STABILITY AND REACTIVITY

---

**Stability Information:** Spontaneous combustion can occur. Stable under normal conditions.  
**Conditions to Avoid:** Heat, flames, sparks Avoid: heat, sparks, flame and oxidizing agents. None known.  
**Chemical Incompatibility:** Oxidizing materials. Strong oxidizing agents. Chlorine. Acids. Strong acids. Metals.  
**Hazardous Polymerization:** Hazardous Polymerization will not occur.

## XI. TOXICOLOGICAL INFORMATION

---

Chemical Name	CAS Number	LD50/LC50
Benzene, 1,2,4-trimethyl-	95-63-6	Inhalation LC50 Rat : 18 gm/m3/4H; Oral LD50 Rat : 5 gm/kg
Mesitylene	108-67-8	Inhalation LC50 Rat : 24 gm/m3/4H
2-Propanol, 1-methoxy-	107-98-2	Inhalation LC50 Rat : 10000 ppm/5H; Oral LD50 Mouse : 11700 mg/kg; Dermal LD50 Rabbit : 13 gm/kg
Cumene	98-82-8	Inhalation LC50 Mouse : 10 gm/m3/7H; Oral LD50 Rat : 1400 mg/kg; Oral LD50 Mouse : 12750 mg/kg; Dermal LD50 Rabbit : 12300 uL/kg
Naphthalene	91-20-3	Inhalation LC50 Rat : >340 mg/m3/1H; Oral LD50 Rat : 490 mg/kg; Oral LD50 Mouse : 533 mg/kg; Dermal LD50 Rabbit : >20 gm/kg
m-Xylene	108-38-3	Oral LD50 Rat : 5 gm/kg; Dermal LD50 Rabbit : 14100 uL/kg
Benzene, ethyl-	100-41-4	Oral LD50 Rat : 3500 mg/kg; Dermal LD50 Rabbit : 17800 uL/kg
p-Xylene	106-42-3	Inhalation LC50 Rat : 4550 ppm/4H; Oral LD50 Rat : 5 gm/kg

## XII. ECOLOGICAL INFORMATION

---

**Overview (for ingredients):** No data available. This material is not expected to be harmful to the ecology.

## XIII. DISPOSAL CONSIDERATIONS

---

**Waste Description for Spent Product:** Mixing spent or discarded material with other materials may render the mixture hazardous. Perform a hazardous waste determination on mixtures. Spent or discarded material is a hazardous waste.

**Disposal Methods:** Comply with all Local, State, Federal, and Provincial Environmental Regulations. Dispose of by incineration following Federal, State, Local, or Provincial regulations. Dispose of in a permitted industrial waste landfill following Federal, State, Local, or Provincial regulations.

**Potential EPA Waste Codes:** If discarded, this product is considered a RCRA ignitable waste, D001.

**Components Subject to USEPA Land Disposal Restrictions:**

Naphthalene	91-20-3	0.71 %
Ethyl benzene	100-41-4	0.24 %

**XIV. TRANSPORTATION INFORMATION**

---

**DOT** PAINT, 3, UN 1263, III  
See 49CFR 172.101 for Special Provisions, Packaging, and Quantity Limitations.

**XV. REGULATORY INFORMATION**

---

<b>Chemical Name</b>	<b>Regulation</b>	<b>CASRN</b>	<b>%</b>
1,2,4-Trimethylbenzene	SARA 313 Reportable:	95-63-6	13.55
Cumene	SARA 313 Reportable:	98-82-8	0.72
Naphthalene	SARA 313 Reportable:	91-20-3	0.71
m-Xylene	SARA 313 Reportable:	108-38-3	0.45
Ethyl benzene	SARA 313 Reportable:	100-41-4	0.24
o-Xylene	SARA 313 Reportable:	95-47-6	0.17
p-Xylene	SARA 313 Reportable:	106-42-3	0.1
Quartz	California Proposition 65 Cancer List:	14808-60-7	0.32
Benzene, ethyl-	California Proposition 65 Cancer List:	100-41-4	0.24
linseed oil	New Jersey Right To Know:	8001-26-1	29.46
aromatic hydrocarbons	New Jersey Right To Know:	64742-95-6	27.09
1,2,4-trimethylbenzene	New Jersey Right To Know:	95-63-6	13.55
Organoclay	New Jersey Right To Know:	68911-87-5	10.5
aromatic hydrocarbons	New Jersey Right To Know:	64742-94-5	6.38

**XVI. ADDITIONAL INFORMATION**

---

**Other Information:** IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HEREUNDER ARE GIVEN GRATIS. NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

MSDS glossary.