



M530-050 Wood Tone Wiping Stain Universal Walnut

MATERIAL SAFETY DATA SHEET

RPM Wood Finishes Group
3194 Hickory Boulevard
Hudson, North Carolina 28638
828-728-8266

EMERGENCY PHONE (CHEM TREC): 1-800-424-9300
FOR ALL INTERNATIONAL TRANSPORTATION ACCIDENTS. 1-703-527-3887 (collect)

Health: 2 Flammability: 3 Reactivity 0

PRODUCT NAME: M530-050 Wood Tone Wiping Stain Universal Walnut

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

REVISION DATE: 31/03/06
SUPERCEDES: 22/07/05
MSDS NO. M530-050
OSHA HAZ. CLASS: Neurotoxin - may cause nervous system damage. Eye irritant.
Hepatotoxin - may cause liver damage. Nephrotoxin - may cause kidney damage.

II. COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	%	CAS #	PEL
Methyl acetate	61-70	79-20-9	200 ppm TWA; 610 mg/m3 TWA
modified alkyd resin non volatiles	11-20	PROPRIETARY	No PEL established
p-chlorobenzotrifluoride	11-20	98-56-6	No PEL established
aromatic hydrocarbons	1-10	64742-95-6	No PEL established
iron oxide red	1-10	1332-37-2	No PEL established
alkyd resin solids	1-10	PROPRIETARY	No PEL established
1,2,4-trimethylbenzene	1-10	95-63-6	No PEL established
aliphatic petroleum distillates	1-10	64742-47-8	No PEL established
Pigment Yellow 74	<1	6358-31-2	No PEL established
Quartz	<1	14808-60-7	see Table Z-3
cumene	<1	98-82-8	50 ppm TWA; 245 mg/m3 TWA
m-xylene	<1	108-38-3	No PEL established
ethylbenzene	<1	100-41-4	100 ppm TWA; 435 mg/m3 TWA
o-xylene	<1	95-47-6	No PEL established
butanol	<1	78-92-2	150 ppm TWA; 450 mg/m3 TWA
p-xylene	<1	106-42-3	No PEL established
carbon black	<1	1333-86-4	3.5 mg/m3 TWA

III. HAZARDS IDENTIFICATION

Routes of Entry: Inhalation., Ingestion., Skin contact., Eye contact., Absorption.

Medical Conditions Aggravated: Persons with reduced pulmonary function may experience breathing difficulty. Pre-existing skin or respiratory conditions. Eye disease. Kidney disease. Liver disease. Skin disease including eczema and sensitization. Digestive tract disease.

Immediate (Acute) Health Effects

Inhalation: Can cause severe central nervous system depression (including unconsciousness). Chronic lung disease (silicosis) and/or lung cancer may result from prolonged/repeated breathing of the dust of this material. Causes respiratory tract irritation. Can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.

Skin Contact: Continued or prolonged contact may irritate the skin and cause a skin rash (dermatitis). Moderately irritating to the skin. Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage. Can cause severe irritation, defatting, and dermatitis. Irritation effects may last for hours or days but will not likely result in permanent damage. No hazard in normal industrial use.

Eye Contact: Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.

Skin Absorption: Toxic and may be harmful if absorbed through the skin; may produce target organ damage. Minimal hazard in normal industrial use. May cause gastrointestinal discomfort.

Ingestion: Harmful if swallowed. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Severely irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea.

Target Organ Acute Toxicity:

Methyl acetate	skin, eyes, respiratory system, CNS
1,2,4-Trimethylbenzene	eyes, skin, respiratory system, CNS, blood
Silica, crystalline	respiratory system, eyes (in animals: lung cancer)
Cumene	eyes, respiratory system, skin, CNS
m-Xylene	CNS, eyes, blood, liver, kidneys, skin, GI tract, respiratory system
Ethyl benzene	eyes, respiratory system, skin, CNS
o-Xylene	CNS, eyes, blood, liver, kidneys, skin, GI tract, respiratory system
n-Butyl alcohol	eyes, CNS, skin, respiratory system
p-Xylene	CNS, eyes, blood, liver, kidneys, skin, GI tract, respiratory system
Carbon black	respiratory system, eyes, lymphatic cancer

Long-Term (Chronic) Health Effects:

Carcinogenicity: ACGIH. IARC. NIOSH. NTP. OSHA. Contains a substance that is a probable cancer hazard based on human studies.

Reproductive and Developmental Toxicity: A component in this product has been shown to cause birth defects and reproductive disorders in laboratory animals at doses that could be encountered in the workplace.

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

Inhalation: Upon prolonged and/or repeated exposure, can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.

Skin Contact:	Prolonged or repeated contact may cause irritation. May cause lingering affects but not likely to result in permanent damage if the exposure is eliminated. Upon prolonged or repeated contact can cause severe irritation, defatting, and dermatitis. May cause lingering affects but not likely to result in permanent damage if the exposure is eliminated.
Eye Contact:	Upon prolonged or repeated contact, dust contact can cause mechanical irritation. Upon prolonged or repeated contact, can cause severe irritation. Eye contact may result in corneal injury. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Temporary vision impairment (cloudy or blurred vision) is possible.
Skin Absorption:	Upon prolonged or repeated exposure, toxic if absorbed through the skin. Likely to cause systemic damage.
Target Organ Chronic Toxicity:	Nervous System. Eyes. Central nervous system stimulation. Kidneys. Liver. Eyes. Respiratory Tract. Kidneys. Liver. Skin. Nervous System. Digestive Tract. Blood.
Supplemental Health Hazard Information:	No additional health information available.

IV. FIRST AID

Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.
Eyes:	Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.
Skin Contact:	Wash with mild soap and water. If irritation occurs get medical attention. If clothing is contaminated, remove and wash before reuse. Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
Ingestion:	If swallowed, do NOT induce vomiting. Give victim 1-2 glasses of water. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting. DO NOT induce vomiting. Get immediate medical attention. Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS.
Notes to MD:	No additional first aid information available.

V. FIRE FIGHTING MEASURES

Flammability Summary:

Flash Point:	9 (CALC.) °F
Upper Flammable/Explosive Limit, % in air:	16.0 @ 77° F
Lower Flammable/Explosive Limit, % in air:	3.0 @ 77° F

Fire Hazards: Container may explode in heat of fire. Dangerous fire hazard when exposed to heat, sparks, flame or oxidants. Material can spontaneously ignite (pyrophoric) when exposed to air at normal or slightly elevated temperatures. Vapors are heavier than air and can travel to a source of ignition and flash back. Combustible Liquid. Can form explosive mixtures at temperatures at or above the flash point. Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.

Extinguishing Media: Water may be ineffective in fire fighting due the material (or component(s)) low flash point, low solvent density, and limited miscibility with water. Alcohol foam Carbon dioxide Water spray Foam Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire.

Fire Fighting Instructions: Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.

Hazardous Combustion Products: Carbon monoxide Carbon dioxide

VI. ACCIDENTAL RELEASE MEASURES

Health Consideration for Spill Response: Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Spill Mitigation Procedures General Methods: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

VII. HANDLING AND STORAGE

Handling: "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Rags or other materials containing this product may oxidize and ignite. All contaminated materials should be isolated immediately to avoid spontaneous combustion. Iron oxide pigments may accelerate this process. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Avoid contact with material. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Minimize dust generation and accumulation. Use spark-proof tools and explosion-proof equipment. Harmful or irritating material. Avoid contact and avoid breathing the material. Use only in a well ventilated area.

Storage: Keep away from heat, sparks, and flame. Keep container closed when not in use. Keep away from sources of ignition. Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed.

VIII. ENGINEERING CONTROLS AND PERSONAL PROTECTIVE EQUIPMENT

Engineering Controls: Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Facilities storing or using this material should be equipped with an eyewash and safety shower. Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

Protective Equipment

Respiratory Tract: Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2-1992). A written respiratory protection program, including provisions for medical certification, training, fit testing, exposure assessments, maintenance, inspection, cleaning, and convenient, sanitary storage should be implemented.

Eyes: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available.

Skin: Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

IX. PHYSICAL DATA

Physical State:	COLORED LIQUID
Odor:	STRONG SOLVENT
Solids Vol %:	19.2382
Solids Wt %:	21.5483
Material VOC lbs/gal:	0.4569
Material VOC gms/l:	54.8665
Coatings VOC lbs/gal:	1.7817
Coatings VOC gms/l:	213.9626
Weight per gallon lbs:	8.3606

VOC data per US EPA guidelines. State and local variations may apply.

X. STABILITY AND REACTIVITY

Stability Information: Normally stable. Keep away from heat, sparks and flame.

Conditions to Avoid: Avoid: heat, sparks, flame and oxidizing agents. High temperatures. None known.

Chemical Incompatibility: Acids. Strong oxidizing agents. Chlorine. Metals. Strong acids. Acetic anhydride. Peroxides. Oxidizing materials.

Hazardous Polymerization: Hazardous Polymerization will not occur.

XI. TOXICOLOGICAL INFORMATION

Chemical Name	CAS Number	LD50/LC50
Acetic acid, methyl ester	79-20-9	Oral LD50 Rat : >5 gm/kg; Dermal LD50 Rabbit : >5 gm/kg

Toluene, p-chloro-alpha,alpha,alpha-trifluoro-	98-56-6	Inhalation LC50 Rat : 22 gm/m3; Inhalation LC50 Mouse : 20 gm/m3; Oral LD50 Rat : 13 gm/kg; Oral LD50 Mouse : 11500 mg/kg
Benzene, 1,2,4-trimethyl-	95-63-6	Inhalation LC50 Rat : 18 gm/m3/4H; Oral LD50 Rat : 5 gm/kg
No data available		
Cumene		
m-Xylene		
Benzene, ethyl-		
sec-Butyl alcohol		
p-Xylene		
Carbon black		

XII. ECOLOGICAL INFORMATION

Overview (for ingredients): No data available. This material is not expected to be harmful to the ecology.

XIII. DISPOSAL CONSIDERATIONS

Waste Description for Spent Product: Spent or discarded material is a hazardous waste.

Disposal Methods: Comply with all Local, State, Federal, and Provincial Environmental Regulations. Dispose of by incineration following Federal, State, Local, or Provincial regulations.

Potential EPA Waste Codes: If discarded, this product is considered a RCRA ignitable waste, D001.

Components Subject to USEPA Land Disposal Restrictions:

Ethyl benzene	100-41-4	0.03 %
n-Butyl alcohol	78-92-2	0.01 %

XIV. TRANSPORTATION INFORMATION

DOT PAINT, 3, UN 1263, II
See 49CFR 172.101 for Special Provisions, Packaging, and Quantity Limitations.

XV. REGULATORY INFORMATION

Chemical Name	Regulation	CASRN	%
1,2,4-Trimethylbenzene	SARA 313 Reportable:	95-63-6	1.16
Aluminum oxide	SARA 313 Reportable:	1344-28-1	0.34
Cumene	SARA 313 Reportable:	98-82-8	0.06
m-Xylene	SARA 313 Reportable:	108-38-3	0.05
Ethyl benzene	SARA 313 Reportable:	100-41-4	0.03
o-Xylene	SARA 313 Reportable:	95-47-6	0.02
sec-Butyl alcohol	SARA 313 Reportable:	78-92-2	0.01
p-Xylene	SARA 313 Reportable:	106-42-3	0.01
Methanol	SARA 313 Reportable:	67-56-1	0.00
Toluene	SARA 313 Reportable:	108-88-3	0.00
Benzene	SARA 313 Reportable:	71-43-2	0.00
Quartz	California Proposition 65 Cancer List:	14808-60-7	0.11
Benzene, ethyl-	California Proposition 65 Cancer List:	100-41-4	0.03
Carbon Black	California Proposition 65 Cancer List:	1333-86-4	0.01
Benzene, methyl-	California Proposition 65 Cancer List:	108-88-3	0.00
Benzene	California Proposition 65 Cancer List:	71-43-2	0.00
Ethyl alcohol	California Proposition 65	64-17-5	0.00
	Developmental Toxicity:		
Toluene	California Proposition 65	108-88-3	0.00
	Developmental Toxicity:		
Benzene	California Proposition 65	71-43-2	0.00
	Developmental Toxicity:		

Benzene	California Proposition 65 Reproductive - 71-43-2	0.00
	Female:	
Methyl acetate	New Jersey Right To Know: 79-20-9	60.52
modified alkyd resin non volatiles	New Jersey Right To Know: PROPRIETARY	16.18
p-chlorobenzotrifluoride	New Jersey Right To Know: 98-56-6	12.45
aromatic hydrocarbons	New Jersey Right To Know: 64742-95-6	2.31
iron oxide red	New Jersey Right To Know: 1332-37-2	1.94

XVI. ADDITIONAL INFORMATION

Other Information:

IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HEREUNDER ARE GIVEN GRATIS. NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

MSDS glossary.