



NCF QUICK Accelerator

ISSUED 8/22/05

## MATERIAL SAFETY DATA SHEET

RPM, WFG.  
3194 Hickory Blvd.  
Hudson, NC 28638  
Phone: 828-728-8266

### 1. PRODUCT IDENTIFICATION

Product Name NCF QUICK  
Part Numbers QA-2 & QA-6  
Product Type AEROSOL ACCELERATOR

### 2. COMPOSITION

Other Ingredients	Chem. Formula	Generic Name(s)	CAS No.	%
N-Hexane			110-54-3	70-75
N,N-Dialkyltoluidine	n/a	n/a	99-97-8	.015-0.016
Ethane, 1,1,1,2-Tetrafluoro			811-97-2	14-10
2-Propanone			67-64-1	10-14

### 3. CHEMICAL AND PHYSICAL PROPERTIES

Appearance: Clear to amber liquid  
Odor: Mild  
Boiling Point: 155°F (68°C)  
pH: Does not apply  
Solubility in Water: Not available  
Specific Gravity Approximately 0.69  
Volatile Organic Compound  
(EPA Method 24) 39% (Base only)  
Vapor Pressure: Approximately 35-45 psig @ 70°F  
Vapor Density: Approximately 2 (Base only)  
Evaporation Rate: (Ether = 1) 1.9

### 4. FLAMMABILITY AND EXPLOSIVE PROPERTIES

Flash Point: Not Applicable  
Autoignition Temperature 232 deg. C 450

Estimated NFPA(R) Code: NFPA is a registered trademark of the National Fire Protection Assn.

Health Hazard: 2

Fire Hazard: 3

Reactivity Hazard: 0

Specific Hazard: Does not apply

Estimated HMIS(R) Code: HMIS is a registered trademark of the National Paint and Coatings Assn.

Health Hazard: 2

Flammability Hazard: 3

Reactivity Hazard: 0

## 5. FIRE FIGHTING MEASURES

Flash Point: No flashpoint (Propellants)

Recommended Extinguishing Agents: Carbon dioxide, foam, dry chemical

Special Firefighting Procedures: Not available

Hazardous Products formed by Fire or Thermal Decomp Irritating organic vapors

Unusual Fire or Explosion Hazards: Cans may explode in fires.

Explosive Limits:

(% by volume in air) Lower	1.2% N,N-Dialkyltoluidine
	1-7% N-Hexane
	1.8% Isobutane
	2.1% Propane
(% by volume in air) Upper	7% N,N-Dialkyltoluidine
	1-7% N-Hexane
	8.4% Isobutane
	9.8% Propane

Compressed Gases: Contents under pressure

Pressure at Room Temp.: 96 psi.

Special Firefighting Precautions/Instructions:

The use of self contained breathing apparatus is recommended of fire fighters. Containers exposed to intense heat from fires must be cooled with water to prevent vapor pressure buildup which could result in container rupture. Keep containers cooled with water and remove them from danger if it can be done with minimal risk. Aerosols can be projectiles when bursting. If aerosols are bursting, stay clear until bursting is complete.

## 5. ACCIDENTAL RELEASE MEASURES

Steps to be taken in case of spill or leak: Avoid flame and sparks. Maintain

adequate ventilation. Soak up in an inert absorbent and store in a closed container until disposal.

## 6. STORAGE AND HANDLING PROCEDURES

Safe Storage: Store away from flame and sparks and below 100F  
Handling: Avoid prolonged breathing of fumes. Avoid skin or eye contact. Always wear recommended personal protective equipment.) Avoid prolonged skin contact. Keep away from eyes. Avoid prolonged breathing of vapors.

## 7. SHIPPING REGULATIONS

DOT (49 CFR 172)  
Domestic Ground Transport  
Proper Shipping Name: Consumer Commodity (Not more than one liter);N-Hexane solution (More than one liter)  
Hazard Class or Division: ORM-D (Not more than one liter); Class 2, Packing Group II (More than one liter)  
Identification Number: None (Not more than one liter); UN 1950 (More than one liter)  
Marine Pollutant: None  
IATA  
Proper Shipping Name: Consumer Commodity (Not more than 500 ml); N-Hexane solution (More than 500 ml)  
Class or Division: Class 9 (Not more than 500 ml); Class 3, Packing Group II (More than 500 ml)  
UN or ID Number: ID 8000 (Not more than 500 ml); UN 1950 (More than 500 ml)  
Label: Miscellaneous Dangerous Goods  
Packaging Instructions: 910

## 8. REACTIVITY DATA

Stability: Stable  
Hazardous Polymerization: Combustion may produce carbon monoxide, carbon dioxide and other unidentified organic compounds.  
Incompatibility: Strong oxidizers  
Conditions to Avoid: Not available  
Hazardous Decomposition Products (non-thermal): None

## 9. EMERGENCY TREATMENT PROCEDURES

Ingestion: Give water to dilute. Do not induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation: Remove to fresh air. If symptoms persist, obtain medical attention.  
Skin Contact: Wash with soap and water.  
Eye Contact: Flush with water for at least 15 minutes. Obtain medical attention.

## 10. PERSONAL PROTECTION

Eyes: Safety glasses or goggles.

Skin: Use protective gloves such as MylarÆ coated Durafab; PVA; or Neoprene.

Respiratory Protection: None required under normal work situations where adequate ventilation is provided. Use NIOSH approved self-contained, positive pressure respirators for emergencies and in situations where air may be displaced by vapors.

Additional Recommendations: Safety shower and eye-wash fountain in immediate area. Personal protective clothing and use of equipment must be in accordance with OSHA standards 29 CFR 1910.133 and 29 CFR 1910.132

## 11. DISPOSAL CONSIDERATIONS

Along with properly characterizing all waste materials, consult state and local regulations regarding the proper disposal of this material.

Do not incinerate cans still under pressure.

## 12. HEALTH HAZARD DATA

Primary Routes of Entry: "Skin contact, Inhalation, Ingestion, and Eye contact."

Signs and Symptoms of Exposure:

Skin: Prolonged and or repeated contact with this solvent can cause irritation of the skin (defatting of skin).

Eyes: Irritant: Liquid contact will irritate eyes and may cause conjunctivitis.

Inhalation: "Dizziness, loss of concentration and irritation. With high exposure levels, effects can include central nervous system (CNS) depression intoxication) and cardiac arrhythmia. Product vapors displace air and can cause suffocation especially in a confined space.

Ingestion: Similar symptoms as for inhalation. Discomfort due to volatility of the solvent would be expected.

Delayed Effects: None currently found.

Existing Conditions

Aggravated by Exposure: None known

Exposure Limits (TWA) Ingredients	ACGIH (TLV)	OSHA (PEL)	OTHER
N-Hexane	50 ppm TWA 180 mg/m3	500 ppm TWA 1800 mg/m3	None
PROPANE	2500 ppm	1000 ppm 1800 mg/m3	None

Exposure Limits (STEL) Ingredients	ACGIH (TLV)	OSHA (PEL)
N-Hexane	50 ppm 1782 mg/m3	None
PROPANE	Asphyxiant	Asphyxiant

Toxicity: Possible eye irritant. Moderately toxic by ingestion.

Estimated dermal LD50 more than 2000 mg/kg.

Primary Routes of Entry: Inhalation, contact.

Signs and Symptoms of Exposure: Vapors irritate eyes, nose and throat.

Liquid is an eye irritant and may irritate skin.

Existing Conditions Aggravated by Exposure: None known

Ingredients	Literature Referenced Target Organ and Other Health Effects	Carcinogen		
		NTP	IARC	OSHA
ACETONE	BLO CNS IRR	NO	NO	NO
N,N-Dialkyltoluidine	ALG MUT	NO	NO	NO

### 13 . HEALTH HAZARD ABBREVIATIONS

N/A Not Applicable	CAR Cardiac
IRR Irritant	KID Kidney
LIV Liver	MET Metabolic
NER Nervous System	CNS Central nervous system
BLO Blood	MUT Mutagen

### 14. REGULATORY INFORMATION

CA Proposition 65: No California Proposition 65 chemicals are known to be present.

IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HEREUNDER ARE GIVEN

GRATIS. NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.