



M840-400 NU GLO LT SCRATCH REMOVER

# MATERIAL SAFETY DATA SHEET

RPM Wood Finishes Group  
3194 Hickory Boulevard  
Hudson, North Carolina 28638  
828-728-8266

EMERGENCY PHONE (CHEM TREC): ..... 1-800-424-9300  
FOR ALL INTERNATIONAL TRANSPORTATION ACCIDENTS. .... 1-703-527-3887 (collect)

Health: 1                      Flammability: 3                      Reactivity 0

PRODUCT NAME: M840-400 NU GLO LT SCRATCH REMOVER

## I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

REVISION DATE: 31/01/06  
SUPERCEDES: None  
MSDS NO. M840-400

## II. COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	%	CAS #	PEL
petroleum process oil	51-60	64742-52-5	No PEL established
aliphatic petroleum distillates	31-40	64742-89-8	No PEL established
aliphatic petroleum distillates	1-10	64742-47-8	No PEL established
Compounded Fragrance	<1		No PEL established
Lemon #136-978			
toluene	<1	108-88-3	200 ppm TWA; C 300 ppm
1,2,4-trimethylbenzene	<1	95-63-6	No PEL established

## III. HAZARDS IDENTIFICATION

**Routes of Entry:** Inhalation., Ingestion., Skin contact., Eye contact., Absorption.  
**Medical Conditions Aggravated:** Persons with reduced pulmonary function may experience breathing difficulty. Pre-existing skin or respiratory conditions. Kidney disease. Liver disease. Eye disease. Skin disease including eczema and sensitization.

### Immediate (Acute) Health Effects

**Inhalation:** Can cause severe central nervous system depression (including unconsciousness). High concentrations in immediate area can displace oxygen and can cause dizziness, unconsciousness, and even death with longer exposure. Can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.

**Skin Contact:** Continued or prolonged contact may irritate the skin and cause a skin rash (dermatitis). Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

**Eye Contact:** Can cause irritation. Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue. Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.

**Skin Absorption:** A single exposure is not likely to result in the product being absorbed through the skin in harmful amounts. Can be absorbed through the skin but exposure must be extensive before adverse health effects occur. Harmful if absorbed through the skin. May cause severe irritation and systemic damage.

**Ingestion:** Irritating to mouth, throat, and stomach. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Harmful if swallowed. Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea.

**Target Organ Acute Toxicity:**

Toluene	CNS, liver, kidneys, skin, eyes, respiratory system
1,2,4-Trimethylbenzene	eyes, skin, respiratory system, CNS, blood

**Long-Term (Chronic) Health Effects:**

**Carcinogenicity:** Contains a substance that is a probable cancer hazard based on human studies.

**Reproductive and Developmental Toxicity:** Possible reproductive hazard.

**Mutagenicity:** No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

**Inhalation:** Upon prolonged and/or repeated exposure, can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.

**Skin Contact:** Continued or prolonged contact may irritate the skin and cause a skin rash (dermatitis). Prolonged or repeated contact may cause irritation. Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

**Eye Contact:** Upon prolonged or repeated contact, can cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.

**Skin Absorption:** Contains methanol. Upon prolonged or repeated exposure, may cause deterioration of the optic nerve if large quantities are absorbed through the skin. Repeated absorption of large quantities may lead to blindness. Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause severe irritation and systemic damage.

**Target Organ Chronic Toxicity:** Nervous System. Kidneys. Liver. Eyes. Skin. Respiratory Tract.

**Supplemental Health Hazard Information:**

No additional health information available.

---

---

**IV. FIRST AID**

- Inhalation:** Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately.
- Eyes:** Immediately flush eyes with plenty of water. Get medical attention, if irritation persists. Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.
- Skin Contact:** Wash with mild soap and water. If irritation occurs get medical attention. If clothing is contaminated, remove and wash before reuse. Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
- Ingestion:** DO NOT induce vomiting. Get immediate medical attention. Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS.
- Notes to MD:** No additional first aid information available.

---

---

**V. FIRE FIGHTING MEASURES**

**Flammability Summary:**

- Flash Point:** 45 (CALC.) °F  
**Lower Flammable/Explosive Limit, % in air:** 7.0 @ 77° F

**Fire Hazards:** Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death. Vapors are heavier than air and can travel to a source of ignition and flash back. Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.

**Extinguishing Media:** Foam Carbon dioxide Dry chemical Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire.

**Fire Fighting Instructions:** Use methods for the surrounding fire. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Apply cooling water to exposed containers well after fire is out. Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling.

**Hazardous Combustion Products:** Carbon monoxide

## **VI. ACCIDENTAL RELEASE MEASURES**

**Health Consideration for Spill Response:** No health effects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section VIII of this MSDS

**Spill Mitigation Procedures General Methods:** No special spill clean-up considerations. Collect and discard in regular trash.

## **VII. HANDLING AND STORAGE**

**Handling:** "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Use spark-proof tools and explosion-proof equipment. Mildly irritating material. Avoid unnecessary exposure.

**Storage:** Keep away from sources of ignition. Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed.

## **VIII. ENGINEERING CONTROLS AND PERSONAL PROTECTIVE EQUIPMENT**

**Engineering Controls:** Check ventilation codes. Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

### **Protective Equipment**

**Respiratory Tract:** Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2-1992). A written respiratory protection program, including provisions for medical certification, training, fit testing, exposure assessments, maintenance, inspection, cleaning, and convenient, sanitary storage should be implemented.

**Eyes:** Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available.

**Skin:** Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

## **IX. PHYSICAL DATA**

**Physical State:** COLORED LIQUID  
**Odor:** OILY HYDROCARBON  
**Solids Vol %:** 54.6988  
**Solids Wt %:** 59.7661  
**Material VOC lbs/gal:** 2.7611  
**Material VOC gms/l:** 331.5831  
**Coatings VOC lbs/gal:** 2.7611  
**Coatings VOC gms/l:** 331.5831

Weight per gallon lbs: 6.8782

VOC data per US EPA guidelines. State and local variations may apply.

## X. STABILITY AND REACTIVITY

**Stability Information:** Stable under normal conditions.

**Conditions to Avoid:** Avoid: heat, sparks, flame and oxidizing agents. None known.

**Chemical Incompatibility:** Strong oxidizing agents.

**Hazardous Polymerization:** Hazardous Polymerization will not occur.

## XI. TOXICOLOGICAL INFORMATION

Chemical Name	CAS Number	LD50/LC50
Toluene	108-88-3	Inhalation LC50 Rat : 49 gm/m3/4H; Inhalation LC50 Mouse : 400 ppm/24H; Oral LD50 Rat : 636 mg/kg; Dermal LD50 Rabbit : 14100 uL/kg
Benzene, 1,2,4-trimethyl-	95-63-6	Inhalation LC50 Rat : 18 gm/m3/4H; Oral LD50 Rat : 5 gm/kg

## XII. ECOLOGICAL INFORMATION

**Overview (for ingredients):** No data available. No ecological information available.

## XIII. DISPOSAL CONSIDERATIONS

**Waste Description for Spent Product:** Mixing spent or discarded material with other materials may render the mixture hazardous. Perform a hazardous waste determination on mixtures. Spent or discarded material is a hazardous waste.

**Disposal Methods:** Comply with all Local, State, Federal, and Provincial Environmental Regulations. Dispose of by incineration following Federal, State, Local, or Provincial regulations. Dispose of in a permitted industrial waste landfill following Federal, State, Local, or Provincial regulations.

**Potential EPA Waste Codes:** If discarded, this product is considered a RCRA ignitable waste, D001.

### Components Subject to USEPA Land Disposal Restrictions:

Toluene	108-88-3	0.4 %
---------	----------	-------

## XIV. TRANSPORTATION INFORMATION

**DOT** Flammable liquids, n.o.s., 3, UN 1993, III (contains )  
See 49CFR 172.101 for Special Provisions, Packaging, and Quantity Limitations.

## XV. REGULATORY INFORMATION

Chemical Name	Regulation	CASRN	%
Toluene	SARA 313 Reportable:	108-88-3	0.4
1,2,4-Trimethylbenzene	SARA 313 Reportable:	95-63-6	0.18
Naphthalene	SARA 313 Reportable:	91-20-3	0.00
Isopropyl alcohol	SARA 313 Reportable:	67-63-0	0.00
Benzene, methyl-	California Proposition 65 Cancer List:	108-88-3	0.4
Toluene	California Proposition 65 Developmental Toxicity:	108-88-3	0.4
petroleum process oil	New Jersey Right To Know:	64742-52-5	59.26
aliphatic petroleum distillates	New Jersey Right To Know:	64742-89-8	30.87
aliphatic petroleum distillates	New Jersey Right To Know:	64742-47-8	8.6

Fragrance	New Jersey Right To Know:		0.5
Compounded Fragrance			
toluene	New Jersey Right To Know:	108-88-3	0.4

## **XVI. ADDITIONAL INFORMATION**

---

### **Other Information:**

IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HEREUNDER ARE GIVEN GRATIS. NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

MSDS glossary.