



Material Safety Data Sheet

SECTION I - IDENTITY

NATURAL PASTE WAX M860-1243
Hazardous -YES

RPM, WFG.
3194 Hickory Blvd.
Hudson, NC 28638
Phone: 828-728-8266

Date Prepared 02-25-05
Health 1
Flammability 2
Reactivity 0
Personal Protection B

SECTION II - HAZARDOUS INGREDIENTS

Table with 7 columns: Hazardous Components, CAS Reg#, PEL, TWA, STEL, Other Limits, % (opt). Rows include Stoddard Solvent and Gum turpentine.

\* ASTERISKED CHEMICAL SUBJECT TO REPORTING REQUIRMENT OF SEC.313 TITLE III.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling point - 32 OF
Vapor Pressure (mm Hg) - 2.0
Vapor Density (air=1) - 4.7
Viscosity (CPS) - NA.
Auto Ignition Temp. - NA.
pH - N.A. +/-
Appearance and Odor - PLIABLE PASTE, SLIGHT PINE ODOR
Specific Gravity(Water-1) - 0.77
Melting Point - 12 OF
Evaporation Rate(Butyl Acetate=1) - 0.21
Decomposition Temperature - NA.
Solubility in Water -NEGLIGIBLE

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point TCC 102 F
Flammable Limits
LEL - 0.7 UEL - 6.0

Extinguishing media -CO2, FOAM, DRY CHEMICAL

Fire Fighting Procedure - COOL CONTAINERS WITH WATER, USE SELF-CONTAINED BREATHING APPARATUS, BURNING PRODUCT IS TOXIC

Fire and Explosion Hazards - CLOSED CONTAINERS MAY BURST WHEN EXPOSED TO EXTREME HEAT. ISOLATE FROM HEAT, SPARKS, OPEN FLAME.

SECTION V - REACTIVITY DATA

Stability -STABLE  
Conditions to Avoid HEAT, SPARKS, OPEN FLAME

Incompatibility - STRONG OXIDIZING AGENTS.  
Hazardous Decomposition or Byproduct - THERMAL DECOMPOSITION MAY YIELD  
CARBON -MONOXIDE.

Hazardous Polymerization - WILL NOT OCCUR  
Conditions to Avoid - N.A.

SECTION VI - HEALTH HAZARD DATA

Routes of entry:

Inhalation - YES                      Skin - YES                      Ingestion - YES

Health Hazards-Acute: CAUSES EYE IRRITATION, DRYING OF SKIN, DIZZINESS,  
NAUSEA. VAPORS MAY BE NARCOTIC. CHRONIC: RESPIRATORY TRACT IRRITATION,  
CUULD DAMAGE LIVER AND KIDNEY.

Carcinogenicity: NO

NTP - N.A.                      IABC Monographs - N.A.                      OSHA Regulated - NO

Sign and Symptoms of Exposure - IRRITATION AND REDNESS OF SKIN,  
DIZZY FEELING, PALE AND NAUSEOUS.

Medical Conditions Aggravated - KIDNEY, LIVER AND LUNG PROBLEMS

Emergency and First Aid Procedures - EYES & SKIN CONTACT: FLUSH WITH PLENTY  
OF WATER. INHALATION: REMOVE TO FRESH AIR, BEGIN ARTIFICIAL RESPIRATION IF  
NEEDED- INGESTION: DO NOT INDUCE VOMITING, GET IMMEDIATE MEDICAL ATTENTION

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled -  
COLLECT MATERIAL INTO METAL CONTAINER. AVOID SPARKS, FLAME, HOT SURFACES.  
WIPE OFF RESIDUE WITH RAG.

Waste Disposal Method - RECYCLE, INCINERATE, OR USE HAZARDOUS WASTE MANAGE-  
MENT FACILITY FOR DISPOSAL ACCORDING TO STATE AND FEDERAL REGULATIONS.  
EPA WASTE NO. D001

Precautions to be Taken in Handling and Storage - COMBUSTIBLE, KEEP  
AHAY FROM HEAT, SPARKS AND OPEN FLAME. USE ADEQUATE VENTILATION. AVOID  
PROLONGED OR REPEATED CONTACT. KEEP CONTAINERS CLOSED.

Other Precautions - STORE IN SECURE AREA. DISPOSE OF EMPTY CONTAINERS SAFELY  
KEEP OUT OF REACH OF CHILDREN

SECTION VXXI - CONTROL MEASURES

Respiratory Protection - USE SELF-CONTAINED BREATHING APPARATUS FOR  
CONCENTRATIONS ABOVE THRESHOLD LIMIT VALUE.

Ventilation                      Local Exhaust -RECOMMENDED.  
   Mechanical                      -ASSURE FRESH AIR CIRCULATION  
   Special                              -N.A.  
   Other                                -N.A.

Protective Gloves - RECOMMENDED: RUBBER  
Eye Protection - RECOMMENDED: GOGGLES  
Other Protection - N.A.

Work/Hygienic Practices - DO NOT EAT/DRINK OR SMOKE NEXT TO MATERIAL.  
WASH HANDS/FACE AFTER WORK.

SECTION IX - TRANSPORTATION
-----------------------------

49 CFR
--------

Unit Cont. - - 30 LB MET PAIL, 4, 1 LB CAN. Report Qty. (Lbs) - NA.  
OSHA - CLASS II. COMBUSTIBLE LIQUID Labels: - FLAMMABLE SOLID  
DOT - HAZARDOUS /X/ FLAMMABLE SOLID-PACKAGING GROUP III  
UN - HAZARDOUS /X/ FLAMMABLE SOLID-PACKAGING GROUP III

DOT: Flammable Solid, n.o.s. (Contains Petroleum Distallites) 4.1, UN1325, PGIII  
UN: Flammable Solid, n.o.s. (Contains Petroleum Distallites) 4.1, UN1325, PGIII  
1 & 4 pound cans=limited quantity 49 CFR 173.151

IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HEREUNDER ARE GIVEN GRATIS. NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.